

OXYGEN™

Ultra-lightweight...
The Oxygen™ safety spectacles protect and provide you with amazing comfort.
Its flat temples fit comfortably under a helmet and remain in place even in extreme conditions.

WEIGHT
21g

FEATURES

- Ultra-enveloping
- Adjustable and non-slip nose
- Lateral protection
- Flat temples



10XY21C
Clear



10XY23C
Clear



10XY23S
Smoke

Reference	Lens Markings	Frame Markings	Lens Treatment	Conformity
○ 10XY21C	2C-1.2  > 1 FT CE	 EN 166 FT CE	Anti-scratch	EN 166 EN 170 Conforms to EN 166: 2001
○ 10XY23C	2C-1.2  > 1 FT CE	 EN 166 FT CE	Anti-scratch/Anti-fog	EN 166 EN 170 EC Type Examination Certificate Number 0958 Issued by Inspec
● 10XY23S	5-2.5  > 1 FT CE	 EN 166 FT CE	Anti-scratch/Anti-fog	EN 166 EN 172

For Lens & frames markings details, please refer to pages 7 to 9 in Swiss one catalogue.
For Lens technologies and colors details please refer to pages 10 to 12 in Swiss one catalogue.

OXYGEN™



DIMENSIONS OF SPECTACLE

Lens Thickness:	2.2mm
Lens Base:	9.5
Lens Size (Diagonal):	72.6mm
Bridge:	-
Temple Length (Lens to tip):	156.0mm
Overall Width:	133.0mm
Closest point between temple tips:	83 +/- 3mm



- 1 Polycarbonate
- 2 NON-P PVC
- 3 Polycarbonate

INSTRUCTIONS FOR USE

- In use ensure that the safety spectacles fit comfortably and securely on the head
- Ensure that the safety spectacles are in place, before entering the hazard area

CLEANING & MAINTENANCE

- The safety spectacles may be cleaned with soap and warm water and dried with a soft cloth
- Do not clean with chemical or abrasive cleaners
- The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature

LIMITATIONS OF USE

- Protection will only be offered if the safety spectacles are fitted correctly
- If the safety spectacles become scratched or damaged they should be replaced, likewise if the safety spectacles are subjected to severe impact they should be replaced immediately
- Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer
- The safety spectacles, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the eye shield and seek medical advice
- The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer
- Oxygen™ is not suitable for protection against dusts, liquids or molten metals

DIMENSIONS OF INNER PACKAGING


Quantity:	10
Weight:	0.49kg



- H Height: 96mm
- L Length: 191mm
- W Width: 284mm

DIMENSIONS OF OUTER PACKAGING

Quantity:	300
(30 display boxes of 10 p)	
Weight: (Approx.)	16.7kg



- H Height: 63cm
- L Length: 98.5cm
- W Width: 30cm

Reference	EAN barcode Unit	EAN barcode inner packaging	EAN barcode outer packaging	Country of origin
10XY21C	7640139971708	5038428325684	5038428288392	Taiwan
10XY23C	7640139971685	5038428325707	5038428288415	Taiwan
10XY23S	7640139971692	5038428325738	5038428288422	Taiwan