

EUROSPECS™

Eurospecs™ combines all the qualities: lightweight, enveloping, lateral and upper protection, adjustable temples enabling a perfect fit for all face types, and a soft non-slip bridge... Maximum protection for incomparable comfort.

WEIGHT



29g

FEATURES

- Soft and adjustable bridge
- Upper protection
- Lateral protection
- Soft and non-slip endtips
- Fully adjustable temples



1EUR23W5
Welding 5

Reference	Lens Markings	Frame Markings	Lens Treatment	Conformity
● 1EUR23W5	5  1FT CE	 EN 166 FT CE	Anti-scratch/Anti-fog	EN 166 EN 169 Conforms to EN 166: 2001 EC Type Examination Certificate Number 78797 issued by BSI

For Lens & frames markings details, please refer to pages 7 to 9 in Swiss one catalogue.
For Lens technologies and colors details please refer to pages 10 to 12 in Swiss one catalogue.

EUROSPECS™



DIMENSIONS OF SPECTACLE

Lens Thickness:	2.0mm
Lens Base:	6
Lens Size (Diagonal):	-
Bridge:	30mm
Temple Length (Lens to tip):	165mm
Overall Width:	145mm
Closest point between temple tips:	66.5mm



- 1 Polycarbonate
- 2 PC & PVC
- 3 PA
- 4 PA & TPR

INSTRUCTIONS FOR USE

- In use ensure that the safety spectacles fit comfortably and securely on the head
- Ensure that the safety spectacles are in place, before entering the hazard area

CLEANING & MAINTENANCE

- The safety spectacles may be cleaned with soap and warm water and dried with a soft cloth
- Do not clean with chemical or abrasive cleaners
- The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature

LIMITATIONS OF USE

- Protection will only be offered if the safety spectacles are fitted correctly
- If the safety spectacles become scratched or damaged they should be replaced, likewise if the safety spectacles are subjected to severe impact they should be replaced immediately
- Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer
- The safety spectacles, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the eye shield and seek medical advice
- The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer
- EUROSPEC™ is not suitable for protection against dusts, liquids or molten metals

DIMENSIONS OF INNER PACKAGING


Quantity:	10
Weight:	0.51kg



- H Height: 96mm
- L Length: 191mm
- W Width: 284mm

DIMENSIONS OF OUTER PACKAGING

Quantity:	300
(30 display boxes of 10 p)	
Weight: (Approx.)	17kg



- H Height: 61.5cm
- L Length: 97cm
- W Width: 29.8cm

Reference	EAN barcode Unit	EAN barcode inner packaging	EAN barcode outer packaging	Country of origin
1EUR23W5	7640139971357	5038428324366	5038428287968	Malaysia