



KNUCKLEHEAD® HAZ-LO® (SPOT) MULTI-PURPOSE WORKLIGHT WITH ARTICULATING HEAD



- Material/Lens** Housing, base and battery housing made from high impact super tough nylon offering exceptional durability. All openings are O-ring sealed for weather resistance. Circular rare-earth magnet surrounded by durable nickel plated steel housing. One-way valve for case venting. Available in orange. Unbreakable polycarbonate lens with silicone anti-scratch coating assembled in a heavy duty bezel. O-ring sealed.
- Dims/Weight** Height: 9.20 in. (23.4 cm); Width: 2.85 in. (7.2 cm); Thickness (at magnet): 2.75 in. (7.0 cm)
 Weight: NiCd: 23.1 oz (655 grams)* Alkaline: 18.3 oz (519 grams)
- Light Source** One C4® LED, impervious to shock with a 50,000 hour lifetime. Single parabolic reflector provides a tighter beam for longer range target illumination
- Output/ Run time** 4 modes:
 - High for a tight, far-reaching beam: 150 lumens; 12,900 candela; 227m beam distance; runs 3.5 hours
 - Low for when less light is ideal and for longer run times; 55 lumens; 4,300 candela; 131m beam; runs 12 hours
 - Moonlight for low-level lighting and extended run times - runs 20 days
 - Flash for signaling - runs 8 hours
- Switch** Rubber dome push-button actuator provides easy operation even when wearing heavy gloves
- Battery** NiCd battery rechargeable up to 1,000 times; also accepts 4 "AA" alkaline batteries
- Features**
- Full 360 degree rotation head with 210 degrees of articulation
 - IPX4 water-resistant; 2m impact resistance tested
 - Removable magnet with 135 lb pull strength
 - Super strong pocket clip
- Approvals** Class I & II Division 1, Groups C,D,F,G; Class III; T-Code: T4; Exia;
 NON-INCENDIVE: Class I Division 2; Groups A,B,C,D, T-CODE T4
 Permissible Flashlight; Approval. No. 20-4140001-0: Tested for Intrinsic Safety in Methane-Air mixtures only. Charge or replace batteries in fresh air only
 Charger meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position
 Meets applicable European Community Directives.
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

| Item | UPC | Part # |
|--|----------------|--------|
| Knucklehead HAZ-LO Spot - 120V AC/12V DC - Yellow | 080926-91727-9 | 91727 |
| Knucklehead HAZ-LO Spot - 120V AC/12V DC - Orange | 080926-91757-6 | 91757 |
| Knucklehead HAZ-LO Spot - 120V AC - Yellow | 080926-91722-4 | 91722 |
| Knucklehead HAZ-LO Spot - 120V AC - Orange | 080926-91752-1 | 91752 |
| Knucklehead HAZ-LO Spot without charger - Yellow (NiCd) (not for sale in EU) | 080926-91721-7 | 91721 |
| Knucklehead HAZ-LO Spot without charger - Orange (NiCd) (not for sale in EU) | 080926-91751-4 | 91751 |
| Knucklehead HAZ-LO Spot - Alkaline - Yellow | 080926-91742-2 | 91742 |
| Knucklehead HAZ-LO Spot - Alkaline - Orange | 080926-91744-6 | 91744 |



| Item | UPC | Part # |
|---|----------------|--------|
| DC2 direct wire charge cord | 080926-22050-8 | 22050 |
| DC1 Charge Cord | 080926-22051-5 | 22051 |
| 100V/120V AC charge cord | 080926-22060-7 | 22060 |
| 230V AC charge cord | 080926-22061-4 | 22061 |
| 240V AC charge cord | 080926-22062-1 | 22062 |
| Steady Charge (SC) Plug-In Charger Holder | 080926-90010-3 | 90010 |
| AC Fast Charger/Holder* | 080926-90011-0 | 90011 |
| DC #1 Fast Charger/Holder* | 080926-90012-7 | 90012 |
| DC #2 Fast Charger/Holder* | 080926-90013-4 | 90013 |
| NiCd Battery Pack | 080926-90335-7 | 90335 |
| Bank Charger (SC) 120V AC | 080926-90400-2 | 90400 |
| Bank Charger (SC) 230V AC | 080926-90600-6 | 90600 |
| Bank Charger 12V DC | 080926-90401-9 | 90401 |
| Alkaline battery carrier (Batteries not included) | 080926-90542-9 | 90542 |

*Not shown