

Technical specs

AN213200XXX

AN213200ADD / AN213200CDD

Name:

ENERGY ABSORBER FALL ARRESTER ON DOUBLE LANYARD - 2M

Description:

Energy absorber fall arrester fitted with 2 textile wrenches webbing 26-29 mm wide and 3 connectors, length: 2m(maximum)

Materials:

100% Polyester

Strong points:

Easy to positioning. Allows important moves.

Available with connecting hook **AM010**



AN213200CDD

Instructions for use:

This strap is recommended for works beyond 6m in height. It is designed to be used with safety karabiners, one of which is fixed to the anchorage point and the other connected to the user's harness. The equipment must be used by one single person at the same time. Choose a resistant anchorage point, 10 kN minimum. Check that the anchorage operation is carried out correctly. Make certain no obstacle impedes strap normal unwinding. The user must always be strapped correctly and the harness properly fixed to the strap end. Before use, check harnesses, karabiners and straps. Sharp edges and corrosion must be excluded. After a fall or every 12 months, return the fall arrester for inspection to the manufacturer or one of his qualified representatives. Replacing parts on fall arresters is strictly forbidden. After a fall, replace the strap. Check that the equipment anchorage point is located above the user or that the general lay-out does not allow any free fall or any pendular movement if a fall occurs. It is recommended to provide every user with a strap.

Limits to use:

Do not use this equipment out of its usage specifications defined in the instructions above. Check that the equipment anchorage point is located above the user or that the general lay-out does not allow any free fall or any pendular movement if a fall occurs. Because of their design, these fall arresters which are connected to the D ring dorsal attachment are only suitable if there is at least a 6-meter clearance from the anchorage point. It is recommended to provide every user with a strap.

Instructions for storage:

Store the equipment in a temperate, dry and ventilated room.

Instructions for cleaning / maintenance:

Clean under water, wipe with a dry cloth and hang it up in a ventilated room.

CE 0082

Performances:

This fall arrester complies with the European directive 89/686, notably regarding design, manufacture and test methods, and with EN355 standard.



ALLSAFE (FZE) SAIF ZONE- PO. BOX 7968 -Sharjah- United Arab Emirates
Tél. : +971 6 557 2285 Fax. : +971 6 557 2286 <http://www.allsafe.ae> E.mail : sales@allsafe.ae

UPDATE : 15/05/2013