

DEDICATED TO YOUR SAFETY

Safe And Efficient Flammable, Toxic And Oxygen Detector

Honeywell RAEGard 3



Honeywell



Dedicated to Your Safety



RAEGuard 3

RAEGuard 3 Series is Honeywell's masterpiece detector of toxic and flammable gas that represents advanced technology and development potential in the future. It provides users with safer, more stable, more reliable and more effective field transmitter, and can be applied in indoor and outdoor hazardous environments, to monitor the dangerous degree of hazardous gases in real time, so as to rapidly and effectively protect the safety of the installation site and production personnel.

The core of RAEGuard 3 — the sensors passed through strict selection and can ensure reliable and stable operation of the transmitter. Combustible gas detector uses catalytic sensor technology with long life (> 5 years) and high anti-poisoning. Toxic and Oxygen detectors adopt a variety of compensatory electrochemical sensor technology, especially Oxygen detector can avoid zero-free (nitrogen) calibration. At the same time, NDIR infrared detection technology with long life, anti-poisoning and Oxygen-free NDIR infrared detection technology allows RAEGuard 3 to be used in a wider and more harsh gas detection environment.



To Your Safety

- All adopt advanced sensor technology
- Wider compensation for temperature and environmental factors keeps the instrument reliable and stable.
- Redundant design to ensure no “false alarm”
- Clear indications of status can perceive the degree of environmental hazards even at long distances.
- Optional integrated visible and sound alarm, light and sound constantly remind, alarm signal will not be ignored
- Optional built-in surge protection device to make sure outdoor installation of “worryfree”
- IP66/67
- TUV SIL2

Self-Management

- Life expiration reminder
- Calibration period expiration reminder
- Alarm, STEL/TWA, fault, warning and other event reminders
- Fault code reminder

Universal Transmitter

- Simplified and reduced cost of installation
- Decreased material management
- Reduced user's spares and training
- Minimal maintenance required

Easy to Use

- Easy read backlit LCD with text, bar graph, digits and icons, support EN and CN
- 3 high-recognized and visible LED status indicators
- 3-wire 4-20mA current output can be fine-tuned to avoid the signal attenuation caused by wiring
- Optional HART® communications as standard for remote diagnostics/configuration
- Optional Bluetooth® for easy remote operation and maintenance via mobile app
- RS485 Modbus RTU for multi-drop networking and remote real-time monitoring
- Local or remote sensor installation options



Cost Effective

Easy to Install



Certification

- EU: CE, EMC, ATEX
- IECEx
- TUV SIL2

Applications

- Oil & Gas
- Chemical industry
- Oil & Gas Storage and Transportation
- Food/beverage
- Refineries
- Power plants
- Steel plants
- Laboratory
- Waste water facilities
- Utilities
- Pharmaceutical plant
- Chemical Storage
- Automotive industry

Technical specifications

RAEGuard 3 Gas Detector	
Use	Universal transmitter with standard configuration of 3-wire, 4-20mA and RS485 MODBUS output for use with a wide range of applications for the detection of flammable, toxic and Oxygen gas hazards.
Electrical parameters	
Input Voltage Range	16-32VDC (24VDC nominal)
Max Power Consumption	Electrochemical Cells: 5.5 watts; Catalytic or NDIR: 7.5 watts
Current Output	Completely configurable 4~20mA (source type) with optional HART® 7.2 protocol as following as default configurations of current output. 1mA Fault 2mA Inhibit (during configuration or setup) 3mA Warning 4mA~20mA Normal 22mA Overrange Note: When the current output is less than 3mA, HART communication will not work properly.
Terminals	5 terminals (14 terminals for use with relay output), wire diameter 0.5mm2 (20AWG) to 2.5mm2 (13AWG)
Relays	3 x 2A@30VDC. Selectable normally open or normally closed and energised/de-energised(programmable) and latch/non-latch Alarm relays default energised/non-latch. Fault relay default energised/non-latch
Communication	RS485, Modbus RTU Optional Bluetooth
Construction	
Transmitter Housing Material	Aluminum Alloy or 316 Stainless Steel
Sensor Housing Material	316 Stainless Steel
Weight (Approx)	Aluminum Alloy: 3.0kg; Stainless Steel: 5.0kg
Mounting	Integral mounting plate with 4 x mounting holes suitable for M8 to fit onto Wall or Pipe
Entries	2 x 3/4’’ NPT cable/conduit entries and 1 x M25 sensor entry. 1 x plug supplied for use for only 1 entry used. Seal to maintain IP rating
Performance****	
Repeatability	<2%
Response Time(T90)	Depending on the gas being detected
Certification	
European	ATEX: LEL/NDIR: CE2460 Ⓜ II 2G Ex db IIC T6 Gb Ta = -40°C to +65°C Toxic and Oxygen: CE2460 Ⓜ II 2G Ex db ia IIC T6 Gb Ta = -20°C to +55°C
International	IECEx: LEL/NDIR: Ex db IIC T6 Gb Ta = -40°C to +65°C Toxic and Oxygen: Ex db ia IIC T6 Gb Ta=-20°C to +55°C
China	LEL/NDIR: Ex d IIC T6 Gb Ex tD A21 IP66 T85°C Toxic and Oxygen: Ex d ia IIC T6 Gb Ex tD A21 IP66 T85°C CCCF, CPA
India	CCOE/PESO
EMC	EN50270:2015, IEC61000-4-5
Performance**	IEC 60079-29-1, EN 50104 IEC 61508 (SIL Assessment, SIL2)
Surge Immunity	Optional Surge Protection Device, Compliance with GB/T 17626.5-2008/IEC61000-4-5:2005, Meets “Installation Class 4”
Environmental	
IP Rating	Toxic and Oxygen: IP66/67 LEL/NDIR: IP66
Operating Temperature***	-40°C~+70°C
Operating Humidity	LEL/NDIR: 0~95%RH (Non-condensing) Toxic and Oxygen: 15%~95%RH (Non-condensing)
Operating Pressure	90~110kPa
Storage Conditions	-20°C~+50°C, 45-75%RH(Non-condensing), in clean air

Remarks:

* RAEGuard 3 will provide users more communication interfaces and gas types in the future, such as wireless. For availability, please contact Honeywell Analytics.

** Availability for SIL2 certificate, please contact Honeywell Analytics.

*** Catalytics and NDIR-CH4 sensor can work continuously at $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$; toxic and oxygen sensor can work continuously at $-20^{\circ}\text{C} \sim +55^{\circ}\text{C}$, intermittently at $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$ (The accuracy and response time of sensors operating in this temperature range will be affected, and long-term operation may lead to sensor sensitivity decline or even damage.)

**** The performance characteristics of the products mentioned above are typical results tested in an environment with a temperature 20°C and a humidity of 50% RH. When calibrating, use the calibration cap and recommended flow for detection. If the sunshade/deluge cover is used instead or the detection is carried out at low temperature, the response time will be slowed down.

FGM-6a00b, "a" indicates sensor type, includes 1(LEL), 2(NDIR), 3(EC). "b" indicates material of main housing, includes S (stainless steel) and blank(aluminum alloy).

Installation

RAEGuard 3 Series detector is designed for use in potentially explosive atmosphere. The installation of detectors should ensure their explosion-proof performance and strictly follow the relevant national standards, to use industrial-grade armored cables and explosion-proof glands and conduits.

Use 0.5mm² (20AWG) to 2.5mm² (13AWG) cross sectional area cable as needed to ensure minimum operating voltage at the detector, depending on installed cable length.


Other Accessories



Sunshade/delug



Collecting Cone



Gas Flow Adapter



Mounting Plate Kit

Electrical

RAEGuard 3 transmitter only provides source current output. The maximum supported cable length can refer to the recommended values in the User's Manual.

Customer Business Center

Service Hotline: 400-815-3366 800-810-1336
www.honeywellanalytics.com



Honeywell Analytics

Building #1, 555 Huanke Road Zhangjiang Hi-Tech
Park Pudong New Area Shanghai, China
Tel: 021-80386800
Fax: 021-60246070

RAE Systems (Beijing) Inc

A1 Building, C&W Industry Zone, No.14 Jiu Xian-
qiao Road, Chaoyang District, Beijing
Tel: 010-56696000
Fax: 010-57560599

Honeywell Analytics

6F-2, No.8, Ziqiang S. Road, Chupei City 30264,
Taiwan
Tel: +886-2-29569986
Fax: +886-3-6576499

Technical Services

Greater China: gaschina@honeywell.com
Taiwan: analytics.tw@honeywell.com
Europe, Middle East and Africa: ha.emea.service@
honeywell.com
America: ha.us.service@honeywell.com
www.honeywell.com

India

Honeywell International India Pvt. Ltd.
Unitech Trade Center, Sector - 43,
Block - C, Sushant Lok - 1,
Gurgaon - 122002, Haryana, India
Tel: +91 124 4971930
Fax: +91 124 4752750

Asia Pacific

Honeywell Analytics Asia Pacific
#508, Kolon Science Valley (I)
187-10 Guro-Dong, Guro-Gu
Seoul, 152-050 Korea
Tel: +82 (0)2 6909 0300
Fax: +82 (0)2 2025 0329

Middle East, Africa,

Life Safety Distributor AG
Javastrasse 2
8604 Hegnau
Switzerland
Tel: +41(0)44 943 4300
Fax: +41(0)44 943 4398

Please note: While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

Brochure_RAEGuard 3_V2020_EN
© 2020 Honeywell Analytics

**THE
FUTURE
IS
WHAT
WE
MAKE IT**

Honeywell