

## Reliable protection elasticity and comfort

- Thin elastic formulation and dexterity
- Comfortable fit and easy to slip on
- Fully textured to improve grip
- Designed for multipurpose applications across all verticals
- Available across a broad selection of sizes



### Industries

- Food Processing

### Recommended For

- Inspection, selecting, checking parts
- Adjusting parts and systems
- Transferring liquids
- Sample taking and processing
- Catering
- Food processing and handling



## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

	82-144
Material	Natural Rubber Latex
Color	Natural
Glove Design	Chlorinated, Fully Textured
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 9001:2008
Regulatory/Standards Compliance	ASTM D3578, EAC TP TC 019:2011, EC 2023/2006, EN ISO 374-1:2016, EN 374:2003 Low Chemical Resistant, EN 374:2003 Microorganism, EN 420:2003 + A1:2009, EN ISO 374-5:2016, FDA21 CFR 177-2600, ISO 9001
Packaging	100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
User Needs Segment	Multi-Purpose
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Sensitisers	<ul style="list-style-type: none"> <li>Zinc Dibutyldithiocarbamate (ZDBC)</li> <li>Zinc Diethyldithiocarbamate (ZDEC)</li> </ul> <p><i>Only a very small number of users may be sensitized to this ingredient in the glove and hence may develop irritant and/or allergic contact reactions.</i></p>

### PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767, EN420
Freedom from Holes (Inspection level I)	4.0 AQL		ASTM D5151, EN 374-2
Palm Thickness (mm/mils)	0.09 / 3.5		ASTM D3767, EN420
Finger Thickness (mm/mils)	0.12 / 4.7		ASTM D3767, EN420
	<b>BEFORE AGING</b>		<b>AFTER AGING</b>
Ultimate Tensile Strength (MPa)	18	14	ASTM D412 & D573
Elongation at Break (%)	650	500	ASTM D412

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### Asia Pacific Region

Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jalan Teknokrat 6  
63000 Cyberjaya  
Selangor, Malaysia  
T: +603 8310 6688  
F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 210  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited  
Level 3, 678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Russia

Ahcenn PYC  
123610 Pochcnp, Mockba  
Kpachonpechehckar  
Ha6. 12, n.3, op. 1304A  
Ten. +7 495 258 13 16

### Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.