MID PEAK - WHEEL RATCHET - NON-VENTILATED

TECHNICAL SPECIFICATION

PRODUCT CODE: AJE170-00 - 00

EVO3® IS A TRUE EVOLUTION OF THE LONG ESTABLISHED MK2 & MK3 HELMETS

HEAD PROTECTION

SHELL:

INSTRUCTIONS FOR USE


Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

CHAMLON™ SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested



WEBBING HARNESS:

HDPE Strap & Webbing Clips with Polyester Webbing Straps



WHEEL RATCHET:

The Revolution® Wheel Ratchet RE is the new easy to use wheel ratchet adjustment system to create a firm comfort fit with added security





CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature

CONFORMITY

Conforms to EN397, EN50365, ANSIZ89 & ΓΟCT P 50460-92

EU Type Examination Certificate number 676976

EN 50365 for Helmets for use in low voltage installations

Meets the retro reflective performance requirements of EN12899 when fitted with CR2 Reflective kit

Meets optional Molten Metal Splash performance

Meets optional Electrical Insulation requirements

Wide size range. Slip or wheel ratchet - High comfort fit

Available vented or unvented. Available with mid or micro peak

Company personalisation available by printing

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com.





















TECHNICAL **SPECIFICATION**

HEAD PROTECTION


PRODUCT CODE: AJE170-00 - 00

EVO3® IS A TRUE EVOLUTION OF THE LONG ESTABLISHED MK2 & MK3 HELMETS

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

3.8kg (Approx.) Weight:



DIMENSIONS OF HELMET

Size: 530 - 640mm

240mm

Weight: 375g (Approx.)



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet










01 White 02 Yellow 05 Blue

06 Red

HEIGHT: 450mm



LIMITATIONS OF USE

Rear

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com .

















