



SFFECO Portable Carbon Dioxide Fire Extinguishers are known for its high reliable performance and ease of handling. The cylinder for CO₂ Fire Extinguishers are seamless and extruded from high grade Chrome Molybdenum Steel or Manganese Steel or Carbon Steel.

Carbon Dioxide is discharged as a white cloud of snow which throttles a fire by eliminating the oxygen. Designed to protect areas where class B (flammable liquids and gases) or Electrical class of fires could occur.

Class of Fire



Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.



Fires on electrical plants.



Note:

Model CD5G and CD6G are SASO Approved

Model	CD 3-G	CD 5-G	CD 6-G	CD 5-L	CD 10-L
Capacity	3 Kg	5 Kg	6 Kg	2.27 Kg	4.54 Kg
Total Weight	10.5 Kg	16.3 Kg	18.7 Kg	8.45 Kg	15.35 Kg
Total Height (mm)	675	755	790	640	705
Total Width (mm)	175	190	190	170	190
Cylinder Height (mm)	580	600	675	540	600
Cylinder Diameter (mm)	115	145	145	100	145
Hose Length (mm)	Only horn	1220	1220	Only horn	1220
Maximum Effective Range (m)	5	5	5	5	5
Duration of Discharge (Sec)	9-11	9-11	9-11	7-9	9-11
Extinguishing Agent	CO ₂				
Testing Pressure (Bar)	250				
Coating	Electrostatic Polyester Powder				
Storage Temperature	-20°C to +60°C				

In line with our policy of continuous product improvement, SFFECO reserves the right to modify specifications without prior notice.