



SURVIVOR®

RIGHT ANGLE, SAFETY-RATED FIREFIGHTER'S FLASHLIGHT



Custom designed optic with optional, interchangeable Smoke-Cutter® plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare

- Material/Lens** Housing, base and battery housing made from high impact super tough nylon offering exceptional durability. All openings are O-ring sealed for weather resistance. Spring loaded clip with built in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One way valve for case venting. Available in international safety orange, high visibility yellow or black
- Dims/Weight** Height: 7.06 in. (17.92 cm); Height in charger: 8.67 in. (22.02 cm); Width: 2.85 in. (7.24 cm); Diameter: 2.87 in. (7.29 cm) Grip area: Height: 3.6 in. (9.14 cm); Thickness: 1.35 in. (3.43cm); Width: 2.20 in. (5.59 cm)
NiCd/NiMH: 18.0 oz (510 grams) Alkaline: 13.7 oz (388 grams)
- Light Source** White LED, impervious to shock with a 50,000 hour lifetime
Custom "Total Internal Reflection" optic for narrow beam and optimum peripheral illumination. Insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.
- Output/Run time** Four lighting modes:
- High for a super-bright beam that pierces through smoke: 41,000 candela; 175 lumens; 405m beam distance; runs 3.5 hours (NiCd/NiMH); runs 4 hours (alkaline)
 - Low for bright light and longer run time: 14,000 candela; 60 lumens; 237m beam distance; runs 13 hours (NiCd/NiMH); runs 15 hours (alkaline)
 - Flash for signaling: runs 8 hours
 - Moonlight mode provides low-level lighting for battery conservation: runs 20 days
- Switch** Rubber dome push-button actuator provides easy operation even when wearing heavy gloves
- Battery** Rechargeable NiCd battery (230V/240V models use NiMH battery); also accepts 4 "AA" alkaline batteries
- Features**
- Reduced bezel length to minimize snag hazards
 - Updated clip design for easy attachment on turnout gear
 - IPX4 water-resistant; 2m impact resistance tested
 - Super strong pocket clip
- Approvals*** Class I, II, Division 1, Groups C, D, E, F, G; Class III, T-Code: T4
Class I, Division 2, Groups A, B, C, D; T-Code: T4
Flashlight meets 500°F requirements of NFPA 1971-8.6 (2013).
Charger meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position.
MSHA: Permissible Flashlight, Approval No. 20-A150001-0.
CEC Compliant (Fast and Smart charger models only)
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

ITEM	UPC	ITEM #
Survivor - 230V AC/12V DC - Yellow NiCd - C1D1	080926-90515-3	90515
Survivor - 230V AC/12V DC - Black NiCd - C1D1	080926-90525-2	90525
Survivor - 230V AC/12V DC - Orange NiCd - C1D1	080926-90505-4	90505
Survivor - 240V AC/12V DC - Yellow NiCd - C1D1	080926-90516-0	90516
Survivor - 240V AC/12V DC - Orange NiCd - C1D1	080926-90506-1	90506
Survivor - 240V AC/12V DC - Black NiCd - C1D1	080926-90526-9	90526
Survivor - 120/100V AC/12V DC Smart Charge - Orange NiCd - C1D1	080926-90503-0	90503
Survivor - 120/100V AC/12V DC Smart Charge - Yellow NiCd - C1D1	080926-90513-9	90513
Survivor - 120/100V AC/12V DC Smart Charge - Black NiCd - C1D1	080926-90523-8	90523

ITEM	UPC	ITEM #
Survivor - 120V AC Fast Charge - Yellow NiCd - C1D1	080926-90512-2	90512
Survivor - 120V AC Fast Charge - Orange NiCd - C1D1	080926-90502-3	90502
Survivor - 120V AC Fast Charge - Black NiCd - C1D1	080926-90522-1	90522
Survivor - 12V DC - Yellow Fast Charge NiCd (not for sale in EU) - C1D1	080926-90519-1	90519
Survivor - 12V DC Fast Charge - Black NiCd (not for sale in EU) - C1D1	080926-90528-3	90528
Survivor - 12V DC Fast Charge - Orange NiCd (not for sale in EU) - C1D1	080926-90509-2	90509
Survivor - (WITHOUT CHARGER) - Yellow NiCd (not for sale in EU) - C1D1	080926-90510-8	90510
Survivor - (WITHOUT CHARGER) - Orange NiCd (not for sale in EU) - C1D1	080926-90500-9	90500
Survivor - (WITHOUT CHARGER) - Black NiCd (not for sale in EU) - C1D1	080926-90520-7	90520
Survivor Alkaline Model - Yellow	080926-90541-2	90541
Survivor Alkaline Model - Orange	080926-90540-5	90540
Survivor Alkaline Model - Black	080926-90545-0	90545

*Approvals do not apply to 230V/240V configurations.



Item	UPC	Part #
DC2 Direct Wire Charge Cord	080926-22050-8	22050
DC1 Charge Cord	080926-22051-5	22051
100V/120V AC Charge Cord	080926-22060-7	22060
230V AC Charge Cord	080926-22061-4	22061
240V UK AC Charge Cord	080926-22062-1	22062
240V AUS AC Charge Cord	080926-22048-5	22048
Steady Charge (SC) Plug-In Charger Holder	080926-90010-3	90010
Fast Charger/Holder	080926-90118-6	90118
DC #1 Fast Charger/Holder	080926-90012-7	90012
DC #2 Fast Charger/Holder	080926-90013-4	90013
Smart Charger Charger/Holder	080926-90116-2	90116
NiCd Battery Pack (not for sale in EU)	080926-90130-8	90130
NiCd Battery Pack (not for sale in EU)	080926-90335-7	90335
Div 2 NiMH Battery Pack (not C1 D1)	080926-90336-4	90336
Bank Charger (SC) 120V AC	080926-90400-2	90400
Bank Charger (SC) 230V AC	080926-90600-6	90600
Bank Charger 12V DC	080926-90401-9	90401
Alkaline Battery Carrier (batteries not included)	080926-90542-9	90542