

69-318

Lightweight Latex Exam Glove with Enhanced Tactility

Designed for comfort, tactility and gripping delicate instruments

- Soft, elastic latex material provides exceptional comfort
- Thin, lightweight design for enhanced tactile sensitivity
- Textured fingers enable easier handling of small objects and delicate tools
- Complies with FDA food handling requirements
- Also available in vend pack (except EMEA)

TouchNTuff 69-318 Gloves

Industries

- Life Sciences
- Food Processing
- Chemical

Recommended For

- Sample taking and processing
- Testing
- Vehicle maintenance
- Food contact
- All food processing, applications that have food contact
- Food processing and handling
- Meat, Fish and Food Processing
- Secondary food processing

WWW.ANSELL.COM

69-318

Lightweight Latex Exam Glove with Enhanced Tactility

Technical Data Sheet

Product Information

69-318

Material	Natural Rubber Latex
Color	Natural
Glove Design	Chlorinated, Powder-Free, Silicone Free, Textured Fingers
Cuff	Beaded

Manufacturing/QMS Audit Standards	ISO 9001:2008
Regulatory/Standards Compliance	Category III, EAC TP TC 019:2011, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN ISO 374-5:2016, EN 374:2003, FDA21 CFR 177-2600, ISO 9001, ISO 13485
Packaging	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
User Needs Segment	Multi-Purpose
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Anti-static	Not Tested
Vulcanization Chemical Accelerators	<ul style="list-style-type: none"> • Zinc Diethyldithiocarbamate (ZDEC) • Zinc Dibutyldithiocarbamate (ZDBC) • Natural rubber proteins <p>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</p>

Physical Properties

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767, EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151, EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767, EN 420
Finger Thickness (mm/mils)	0.14 / 5.5		ASTM D3767, EN 420
	Before Aging After Aging		
Ultimate Tensile Strength (MPa)	≥ 18	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 650	≥ 500	ASTM D412

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	69318060	69318070	69318080	69318090	69318100

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

- Ansell Healthcare Europe NV
- T: +32 (0) 2 528 74 00
- F: +32 (0) 2 528 74 01

Asia Pacific Region

- Ansell Global Trading Center
(Malaysia) Sdn Bhd
- T: +603 8310 6688
- F: +603 8310 6699

North America Region

- Ansell Healthcare Products LLC
- T: +1 800 800 0444
- F: +1 800 800 0445

Latin America & Caribbean Region

- Ansell Commercial Mexico S.A. de C.V.
- T: +52 442 248 1544 / 248 3133

Australia

- Ansell Limited
- T: +61 1800 337 041
- F: +61 1800 803 578

Russia

- Ansell PYC
- Ten. +7 495 258 13 16

Performance Standards and Regulatory Compliance

☐
K P T

☐
EN374_LowChemicalResistance

☐
EN 374 Microorganism

☐

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

☐