

FIRE FIGHTING GLOVES



MATERIALS

- Outer shell: Treated premium split and durable Eversoft® cowhide on the top and palm.
- The palm is reinforced to increase the durability and movement when using tools, hoses, and ropes on all both wet and dry application.
- moisture barrier: Polyurethane – Porelle® Breathable and water proof moisture barrier.
- Inner Liner: Kovenex® - Flame and Thermal resistance liner

DESIGN & FEATURES

- 3D Design.
- Roll-over seamless fingertips design for maximum flexibility and dexterity.
- Curved and forchettted fingers design with fold over feature.
- Keystone thumb design for more freedom on hand movement.
- Moisture & inner liners are sewn and bonded together to ensure retention after using.
- Durable in washing and wearing.
- Lather hang loop inside.

STYLES

- Wristlet Style : Made from two layers of KEVALR® with lather pull-tab cuff.
- Gauntlet Style : Easy to wear with turnout gear which has built-in wristlets.

COLOR

Gold color with black on palm & tiptoes areas.

SIZES

Available on sizes From S To XXXL.

PERFORMANCE STANDARDS & COMPLIANCE

- NFPA 1971 - Protective Ensembles for Structural Fire Fighting – Latest Edition.
- SEI – SAFETY EQUIPMENT INSTTUE – ASTM INTERNATIONAL.



FIRE CLAW™



FIRE PAW™



PRE-USE INFORMATION

This protective glove is designed to provide limited protection against injuries to the hand when properly worn. It is for conventional fire fighting and safe for use ONLY by trained, experienced Fire Fighters who use caution at ALL TIMES.

The user of protective gloves must have the background and training necessary to select the right product. Chief Technologies LLC has no control over how the customer may put to use.

For additional marking of gloves, use ONLY permanent marker products. DO NOT use heat transfers or bonding of any kind.

Performance properties of this glove specified in the NFPA standards cannot be tested by the user in the field. Inspect gloves regularly.

If the substandard performance is due to a manufacturing defect, Chief Technologies LLC will replace the glove or the gloves. Defective products must be returned to Chief Technologies LLC for evaluation by the Quality Control Department.

Chief Technologies LLC warrants that its fire fighter gloves are free from defects in material and workmanship for the useful life of the product. This warranty specifically excludes accidental damage (acid, tears on nails, etc.), intentional or unintentional abuse, natural disasters, damage caused by disregard of care instructions, and normal wear. In order to maximize the useful life of these products and maintain the warranty, the products are to be used only by appropriately trained personnel following proper firefighting or emergency response techniques and in accordance with the product's warning, inspection, maintenance, care storage and retirement instructions. Failure to do so will void the warranty.

PREPARATION FOR USE

Chief Technologies LLC offers protective gloves in multiple sizes. Only wear products of a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimum level of protection. The size of the protective gloves is marked on inside label. Gloves are available in the following sizes:

| NFPA size | 64N | 70N | 70W | 76N | 76W | 82N | 82W | 82XW |
|-------------------|-----|-----|-----|-----|-----|-----|-----|------|
| MANUFACTURER SIZE | XXS | XS | S | M | L | XL | XXL | XXXL |

DONNING/DOFFING

Put gloves on securely by using pull area at wristlet or glove body. Do not pull-on hem material. For maximum fingertip dexterity, ensure that the middle three fingers go to the ends of the fingertips of the glove body. Remove gloves carefully. Only wear gloves that properly interface with coat sleeves.

INSPECTION

All protective gloves should be inspected before and after each use. Possible areas of concern include cut or worn areas; torn seams or broken threads; torn or raveled knit wristlets; blood and/or chemical contamination of the leather and/or liner, which cannot be removed.

Damaged or contaminated gloves must be discarded and replaced. No protective glove can provide optimum protection from all conditions. Use extreme care for all emergency operations. Never use a damaged product. Failure to comply with these instructions may result in serious injury or death.

Periodically wet gloves and inspect linings for water resistance to the innermost surface of the glove. Moisture may be evident inside glove due to perspiration or wicking of the interface area.



MAINTENANCE AND CLEANING

Hand wash with a mild soap and water. DO NOT use chlorine bleach. Tumble dry on a cool setting or shape the glove and air dry. Excess water may be squeezed (NOT wrung) from the leather. DO NOT wear gloves that have not been thoroughly cleaned. Allow gloves to dry after each use or cleaning. Store gloves in a cool dry place.

Gloves may be brushed after use and/or cleaning to remove surface dirt and receive the nap of the leather outer shell.

Decontaminate or dispose of gloves in accordance with procedures set forth for the environment to which the glove has been exposed. Proper decontamination of your protective gloves will depend on the type and extent of contamination. If your protective gloves become contaminated with blood or body fluids, immediately isolate the gloves, and inform your supervisor, department, or organization. Your protective gloves must be subjected to an advanced cleaning using specialized procedures. If your protective gloves become contaminated with chemicals or other hazardous substances, immediately isolate the gloves, and remove them from service, taking care not to cross-contaminate other clothing items. Immediately inform your supervisor, department, or organization. Do not wear protective gloves that were contaminated until verification has been provided that your protective gloves are free from contamination.

Do not attempt to repair your gloves. If damaged, report the damage to your supervisor, department, or organization and obtain a new set of gloves as a replacement.

RETIREMENT AND DISPOSAL

The decision for the continued service of your protective gloves must be made by a qualified individual within your department or organization. If you have any doubts about your protective gloves and their condition, immediately bring this matter to the attention of your supervisor, department, or organization. Protective gloves that are no longer deemed serviceable for reasons of damage, contamination, or other unsafe condition must be disposed of in a fashion (such as cutting them in unusable pieces) whereby the gloves cannot be reused.

The moisture barrier has not been evaluated for all chemicals that can be encountered during fire fighting operations and information that the effects of chemical exposure on the moisture barrier are to be evaluated per the inspection procedures in NFPA 1851.

Proper use consistent with NFPA 1500, Standard on Fire Department Occupational Safety and Health Program, and 29 CFR 1910.132, General Requirements of Subpart I, Personal Protective Equipment.

Save these instructions for reference. READ THE PRE-USE INFORMATION, PREPARATION FOR USE, DONNING/DOFFING, INSPECTION, AND MAINTENANCE AND CLEANING INSTRUCTIONS CAREFULLY. If you have further questions, please contact us.