

Information Data Sheet

Detector Tube **CO-10 (ppm)**

Part No. (US): **487334**

Part No. **D5085821**

1. Application

Detection of carbon monoxide (CO) in air or in technical gases.

2. Detector Tube Sampling Pump

KWIK DRAW (formerly MSA AUER) Gas-Tester® I/H, Gas-Tester® I / ThumbPump™-Sampler, Toximeter® II, Uniphos Kwik-Draw™-Pump or other suitable detector tubes pumps. Observe respective instructions for use.

3. Measuring Range

100 ppm ... 3,000 ppm carbon monoxide at n = 1 (1 stroke)

10 ppm ... 300 ppm carbon monoxide at n = 10 (10 strokes).


Any number of strokes from 1 to 10 can be chosen. For calculation use n=10 scale, relate as follows:

$$\text{ppm CO} = \frac{10 \times \text{indication on n=10 scale}}{\text{no. of strokes chosen}}$$

4. Chemical Reaction and Color Change

Oxidation of carbon monoxide by iodine pentoxide in fuming sulfuric acid.

Color change: White → Brown / green.



5. Ambient Conditions During Sampling

Detector tubes can be used without compensation of the reading between -10 °C and 50 °C (10 °F and 120 °F) and up to 90 % rh (75 g/m³ at 50 °C [120 °F]) water vapour will not affect accuracy of indication.

Water vapour will be absorbed by the protective layer changing its color from brown to yellow. Do not use detector tube if protective layer has totally changed color.

6. Interferences and Cross Sensitivities

a) No interference from:

Methane, carbon dioxide, as well in concentrations above 50 vol.%.

– Hydrogen, ethane up to 10 vol.% (n = 1) or 1 vol.% (n = 10); higher concentrations discolors the whole indicating layer, a sharp stain edge is not formed.

– sulfur dioxide, nitrogen oxide, nitrogen dioxide up to 1 vol.% (n = 1) or 1,000 ppm (n=10).

Manufactured By:

Uniphos Envirotronic Pvt. Ltd (100% EOU)

P.O. Nahuli - 396 108

Tal. Umbergaon,

Dist: Valsad, Gujarat, India

Tel. : +91(260) 2730156 / 57 / 58

Fax : +91(260) 2730160

gasdetection@uniphos-envirotronic.com

Marketing Office:

Uniphos Envirotronic Pvt. Ltd

Readymoney Terrace, 167,

Dr. Annie Besant Road, Worli,

Mumbai 400 018, India.

Tel. : +91(22) 6123 3500

Fax : +91(22) 2493 8826/+91 (22) 2497 8119

www.kwikdrawtubes.com

- b) Propane and higher saturated hydrocarbons, olefinic hydrocarbons, hydrogen sulfide discolors the protective layer from brown to greenish. At least 3,000 ppm (n = 1) or 300 ppm (n =10) of propane, olefinic hydrocarbons (e.g. ethylene) and hydrogen sulfide are retained. Retention is lower for butanes and higher saturated hydrocarbons (e.g. hexanes). Concentrations of hydrocarbons exceeding the protective capacity may be eliminated by adding a charcoal filter tube Ads (804403).
- c) Acetylene is indicated: 1,000 ppm is indicated as approx. 400 ppm CO (n = 1).
- d) Water vapour reduces the protective layer retention capacity, in particular for hydrocarbons.

Manufactured By:

Uniphos Envirotronic Pvt. Ltd (100% EOU)

P.O. Nahuli - 396 108

Tal. Umbergaon,

Dist: Valsad, Gujarat, India

Tel. : +91(260) 2730156 / 57 / 58

Fax : +91(260) 2730160

gasdetection@uniphos-envirotronic.com

Marketing Office:

Uniphos Envirotronic Pvt. Ltd

Readymoney Terrace, 167,

Dr. Annie Besant Road, Worli,

Mumbai 400 018, India.

Tel. : +91(22) 6123 3500

Fax : +91(22) 2493 8826/+91 (22) 2497 8119

www.kwikdrawtubes.com