HAND PROTECTION

CONDOR PERSONAL PROTECTIVE EQUIPMENT OFFERS YOU A WIDE RANGE OF QUALITY GEAR MADE TO MEET OR EXCEED RELEVANT ANSI AND OSHA SAFETY STANDARDS.



COMPLIANCE

OSHA 1910.138(A) GENERAL REQUIREMENTS

Employers shall select and require employees to use appropriate hand protection when employees' hands are exposed to hazards such as those from skin absorption of harmful substances, severe cuts or lacerations, severe abrasions, punctures, chemical burns, thermal burns and harmful temperature extremes.

OSHA 1910.138(B) SELECTION

Employers shall base the selection of the appropriate hand protection on an evaluation of the performance characteristics of the hand protection relative to the task(s) to be performed, conditions present, duration of use, and the hazards and potential hazards identified. For additional information on OSHA standards, please visit: www.osha.gov.



TYPES OF GLOVES

GENERAL PURPOSE

Reduce hand injuries and fatigue while providing excellent grip, flexibility, comfort and abrasion resistance. Uses: Automotive and light assembly, food handling, maintenance, metal/steel industries, warehousing.



LEATHER PALM AND DRIVER'S

Choose from a variety of cowhide, pigskin, goatskin and deerskin gloves for comfort, durability, dexterity and abrasion resistance. Uses: Construction, contractors, gardening, general assembly and maintenance, welding.



2YEH9

CHEMICAL RESISTANT

Protect against a variety of chemicals with excellent abrasion, puncture and tear resistance.

Uses: Aerospace, agriculture, automotive, chemical and food processing, general maintenance, mining, petrochemicals, refining.



CUT AND PUNCTURE RESISTANT

Available in a wide variety of materials that offer different levels of cut, abrasion and puncture resistance against sharp objects, including glass, metal and needles. Uses: Automotive assembly, construction, food industry, glass handling, metal fabrication, parts handling, wood handling.



DISPOSABLE

For one-time use applications; thin gauge thickness provides superior flexibility, sensitivity and dexterity. Uses: Food service, general maintenance, laboratories, medical, pharmaceutical.



MECHANIC'S

Protect workers' hands from impact, nicks and abrasion without sacrificing dexterity or grip for handling tools and parts. Uses: Assembly, mechanics, warehousing, power sports, hand and power tools.



PALM COATED

Offer dexterity, grip and comfort while protecting against snags, punctures and abrasions. Appropriate for use in wet areas where grip and dexterity are critical. Substitute for leather work gloves.

Uses: Automotive and light assembly, construction, maintenance, shipping/receiving.



TEMPERATURE RESISTANT

Protect from extreme hot and cold temperatures. Certain applications depend on weight of product handled and length of time handled.

Uses: Aluminum casting, automotive, cold storage, injection molding, steel manufacturing, stamping.



The Grainger Choice badge signals a broad selection of products that deliver quality and value, brought to you by Grainger.

GLOVE INFORMATION

OSHA REGULATIONS FOR HAND PROTECTION 1910.138(A) GENERAL REQUIREMENTS

Employers shall select and require employees to use appropriate hand protection when employees' hands are exposed to hazards such as those from skin absorption of harmful substances, severe cuts or lacerations, severe abrasions, punctures, chemical burns, thermal burns and harmful temperature extremes.

1910.138(B) SELECTION

Employers shall base the selection of the appropriate hand protection on an evaluation of the performance characteristics of the hand protection relative to the task(s) to be performed, conditions present, duration of use, and the hazards and potential hazards identified.

GLOVE SIZING CHART

Wrap a tape measure around your palm to determine the circumference of your hand in inches. Refer to the sizing chart to determine your appropriate glove size.

PALM SIZE (IN.):	6 to 7	7 to 8	8 to 9	9 to 10	10 to 11	11 to 12
SIZE:	XS	S	М	L	XL	2XL
OTHER SIZES:	Ladies		Men's			
	Universal					
					Jumbo	



ANSI CUT, PUNCTURE AND ABRASION RESISTANCE GUIDE

CHOOSE THE APPROPRIATE LEVELS OF CUT, PUNCTURE AND ABRASION RESISTANCE FOR HAND AND ARM PROTECTION

The ANSI Cut, Puncture and Abrasion Resistance tables below, provided by ANSI, help identify the level of resistance needed in each area, enabling compliance with OSHA regulations 1910.138 (a) and 1910.138 (b), mitigating risk of injury and increasing worker productivity. The ANSI/ISEA 105-2005 standard provides a consistent, numericscale method for manufacturers to rate their products in each of the designated areas. The "level of resistance" numbering has been incorporated into the Grainger catalog to help purchasers and users make informed decisions when choosing gloves and sleeves for each category of protection.

• The ANSI/ISEA 105-2005 standard provides performance classification levels for many different materials based on standardized test methods. ANSI/ISEA: American National Standards Institute and International Safety Equipment Association. For additional information on ANSI standards, please visit: *www.ansi.org.*

LEVEL	WEIGHT (GRAMS) NEEDED TO CUT THROUGH MATERIAL WITH 25MM OF BLADE TRAVEL				
Cut Resistance					
0	< 200				
1	≥ 200				
2	≥ 500				
3	≥ 1000				
4	≥ 1500				
5	≥ 3500				
Note: When tested in accordance with ASTM F1790-97.					

LEVEL PUNCTURE (NEWTONS)

	1 /					
Puncture Resistance						
0	< 10					
1	≥ 10					
2	≥ 20					
3	≥ 60					
4	≥ 100					
5	≥ 150					
Note: When tested in accordance with						

Clause 6.4 on EN 388:2003.

ABRASION CYCLES TO FAIL				
ES TO FAIL				
)				
)				
Note: When tested in accordance with ASTM D3389-05.				

LEATHER GLOVE INFORMATION



CUFF STYLES KNIT WRIST

Seamless, stretchable rib knit is sewn onto glove to provide a comfortable, secure fit. Fits under clothing sleeves to keep cold air out.



SAFETY

Protects wrist and allows easy movement and removal of glove in emergency situations.

2AH54



THUMB STYLES

KEYSTONE

Specially designed 1-piece, inset thumb is double-sewn and has double thickness at this critical wear point. This construction provides extra comfort and allows extra wear.

Mirrors the natural shape of the hand and

offers comfortable gripping and free thumb

laid flat, the thumb should extend to the side.



movement. Provide extended wear. The thumb pattern is easily identified: when the glove is

WING

4YV44

5AJ33

STRAIGHT

Cut as 1 piece with the palm, the thumb extends straight from the wrist. This style uses less material than the similar wing thumb, reducing the cost of the glove.



MATERIALS COWHIDE

Excellent abrasion resistance, breathability and thermal protection.



PIGSKIN

High abrasion resistance and heat protection. Material is flexible and won't stiffen when wet. Suitable for jobs that are exposed to moisture.





Most abrasion resistance. Soft and pliable. Twice as durable as cowhide and pigskin materials. Suitable for jobs where optimal dexterity is important.

DEERSKIN

Features the highest tensile strength. Soft, flexible and long wearing. Suitable for jobs where optimal dexterity is important.

4TJW8



GAUNTLET

Extended cuff provides greater protection of wrist and forearm.



SLIP-ON

Constructed without a cuff, these gloves slip on and off easily. Material extends over the wrist. Primarily used in a driver's, mechanic's or general-purpose gloves.

CUT STYLES

GUNN

Seamless on back for greater comfort; the palm side of the middle 2 fingers is a separate glove pattern and is sewn into the palm at the base of the middle 2 fingers. In leather styles, the seam is reinforced with a welt increasing gloves' durability and wear life.

CLUTE

Seamless palm made from a continuous piece of leather means greater ease of movement, comfortable gripping and a roomy fit. Back of glove has parallel seams. Finger side seams are toward palm side of glove. Primarily used in fabric gloves and lightweight leathers.

3AJ10



MECHANIC'S GLOVE INFORMATION

Gloves are available in a variety of styles to meet the demands of a broad range of applications. Choose gloves with single-layer palms for general tasks, padded palms for impact resistance or patch palms for additional wear and abrasion resistance. PVC-coated palms offer increased grip. Insulated styles are available for hot or cold applications.



HIGH-VISIBILITY MECHANIC'S GLOVES Bright-colored mechanic's gloves help promote awareness and compliance.



42KZ59

BOX-HANDLING GLOVES Mechanic's gloves designed for box-handling applications.



5NGL7

42KZ49

MECHANIC'S GLOVES Clarino® synthetic leather palms and PVC patches improve grip.

ABRASION-RESISTANT

COLD CONDITIONS GLOVES

Mechanic's gloves designed for colder climates.

PALM-COATED GLOVE AND LINER INFORMATION

Choose from a variety of coating material and liner options.



COATING MATERIALS POLYURETHANE

Flexible, synthetic material helps protect hands from harmful residues and chemicals while providing grip and abrasion-resistance. Allows tactile sensitivity.



PVC

Synthetic thermoplastic polymer provides abrasion resistance, tactility and dexterity combined with wet and dry grip. Ideal for applications where wear rates are moderate to high.

3ZL55



NITRILE FOAM

Absorbs oils better than standard nitrile coating and provides grip in oily or greasy applications. Bi-polymer. Combination of nitrile and polyurethane that provides durability, abrasion resistance, softness and dexterity.



NITRILE

A synthetic rubber that resists snags, punctures, abrasions and cuts. Suitable for people with latex allergies; provides resistance to petroleum, acids, and aromatic and chlorinated solvents.

3HB75



NATURAL RUBBER/LATEX

A natural material with elasticity that provides resistance to cuts, punctures and slashes with a safe, secure grip.

LINERS

NYLON

Lightweight lining provides high tensile strength and dexterity.

KNIT

Standard weight lining allows hands to breathe for cool and comfortable extended-wear protection.

BAMBOO

Lighter, softer and more absorbent than cotton or other synthetic materials. Breathable material wicks moisture away from the skin. 100% natural bamboo knit shells are inherently strong, antibacterial, biodegradable and provides UV protection.