



Protect your values.

PYRO-SAFE® DG-CR 1.5

Wraps

Description

Flexible and tear-resistant glass filament fabric composite material with intumescent coating on the inside.

Application Areas

- Fire protection wrap for services with combustible components (e.g. pipes with combustible insulation).
- For indoor and outdoor use.



Delivery and Packaging

PYRO-SAFE® DG-CR 1.5	
Packaging	Cardboard box
Width	125 mm
Length	10 m
Item number	
	01261125

Please contact us for further information:

✉ global@svt.de

Orders: order@svt.de

☎ +49 4105-40 90-0



Protect your values.

PYRO-SAFE® DG-CR 1.5

Technical Data

Shape	Fabric with intumescent coating on the inside.
Coating	Grey outside, anthracite inside
Nominal thickness	1.5 mm
Weight per unit area	2000 g/m ²
Reaction temperature	from approx. 150 °C
Interactions	No influence on other building materials like polyethylene (PE) and polyvinyl chloride (PVC) according to EOTA TR 024.
Application temperature	+ 5 °C – + 50 °C (< + 5 °C reduction of flexibility)
Application instructions	• Apply with standard cutting tools such as scissors or cutter knife. • Can be painted over with approved paints based on acrylic dispersion, alkyd resin, polyurethane acrylic and epoxy resin acc. to EOTA TR 024.
Storage	Dry indoors. Protect from pressure loads.
Safety information	Please observe the safety data sheet.
Declaration of performance (DOP) no.	01261125-PYRO-SAFE® DG-CR 1.5



Protect your values.

PYRO-SAFE® DG-CR 1.5

Applications

Penetration seal

	Certification	System name	Fire resistance class	
	ETA-16/0268	PYRO-SAFE® Novasit BM	max. EI 120	gemäß EN 13501-2
		PYRO-SAFE® Novasit BM 240	max. EI 240	
		PYRO-SAFE® CT	max. EI 120	
		PYRO-SAFE® Novasit BM LTW		
		PYRO-SAFE® Universal EI 120		
		PYRO-SAFE® ES	max. EI 90	
		PYRO-SAFE® Flammotect OSI	max. EI 120	
		PYRO-SAFE® Flammotect 1-lagig	max. EI 90	
		PYRO-SAFE® Flammotect 2-lagig	max. EI 120	
		PYRO-SAFE® Flammotect 4-lagig	max. EI 240	
	Z-19.53-2329	PYRO-SAFE® Flammotect COMBI 90	Feuerbeständig (90 min.)	
	Z-19.53-2482	PYRO-SAFE® COMBI 90 – LTW		
	Z-19.53-2299	PYRO-SAFE® Sibralit ES		
	Z-19.15-1276	PYRO-SAFE® Universalschott COMBI 90		
	Z-19.53-2324	PYRO-SAFE® CT		
	C-AJ-2812, F-A-2278, F-A-5060, W-J-2325, W-J-5188, C-AJ-8274, F-A-8041, F-A-8042, F-A-8043, F-A-8044, F-A-8045, F-A-8046, W-J-8062, W-J-8063, W-J-8064, W-J-8065, W-J-8066, W-J-8067	PYRO-SAFE® DG-CR 1.5	FT-Rating max. 3 hrs.	
GOST DBN / DSTU	upon request	Sealings for wall and ceiling penetrations for flammable pipelines using PYRO-SAFE® DG-CR	EI 150	