

Justrite® Sure-Grip® EX Safety Storage Cabinets offer top performance for flammable liquid storage and protection.

**EXtra safe, EXtra sturdy, EXtra secure**

Fusible links hold doors wide open and melt at 165°F (74°C) for automatic closure (on self-closing models).

Sturdy 18-gauge (1-mm) double wall steel construction with 1-1/2-in (38-mm) of insulating air space.

Easy-close, self-latching doors; U-Loc™ handle (shown below) does not require manual rotation to engage mandatory three-point latch.

Fully welded, not riveted, construction holds squareness for longer life and offers greater protection in a fire since air gaps are reduced.

Continuous piano hinge provides smooth closure.

Durable and chemical-resistant, lead-free powder-coat paint finish, inside and out, retains high gloss look and minimizes the effects of corrosion and humidity.

Dual vents with built-in flash arresters strategically placed at bottom and opposite top.



45-gallon (170-liter) self-close door style

Concealed self-close mechanism provides obstruction-free access to top shelf space. Self-indexing doors guarantee they will close in sequence and ensure a tight closure from top to bottom (on self-closing models). Patent pending

Patented SpillSlope® safety shelves direct spills to back and bottom of leakproof sump. Adjustable on 3-in (76-mm) centers, they meet ANSI standards with a 350-lb (159-kg) safe allowable load.

Welded shelf hangers interlock with shelf to offer maximum "nonslip" stability with no flimsy brackets to lose.

2-in (51-mm) leakproof containment sump holds leaks and meets EPA requirements.




Adjustable leveling feet make it easy to balance cabinets on uneven surfaces.



Built-in grounding connector (on outside side panel) for easy grounding. Shown here with optional ground wire 08500.



**Complies with OSHA 29 CFR 1910.106 and NFPA Code 30, section 9.5.3; FM Approved**



Stainless steel, 3-point bullet self-latching system provides easy, fail-safe, positive door closure with increased heat resistance. Patent pending



Easily secure your contents—U-Loc™ handle includes double key set or can be padlocked (not included) for greater security. Patent pending



Patented SpillSlope® safety shelves direct spills to back and bottom of leakproof sump; adjust on 3-in (76-mm) centers for versatile storage. Meets ANSI MH28.1



Welded construction holds squareness for long life; door astragal provides extra sturdiness.



Highly visible HazAlert™ reflective label provides warning—"Flammable – Keep Fire Away" in English, Spanish, and French.

## How to Select A Safety Cabinet

### Size and type of container:

Determine if you are storing safety cans, 30- and 55-gallon (110- and 200-L) drums, smaller paint cans, 1 quart (4-L) bottles, aerosols, dispenser cans or other containers.

### Capacity:

Select specialty cabinets for on-the-spot needs; larger cabinets for expanded or large quantity storage.

### Type of chemical:

Easily identify, organize and segregate liquids by using the correct color cabinets.

### Door style

Select from **manual** or **self-closing** door style cabinets. Cabinets with self-closing doors provide an extra measure of protection. Since the human element of remembering to close the door is neutralized by the automatic closing feature.

#### Manual

Economical manual-close doors permit doors to open a full 180 degrees. When pushed closed they will automatically self-latch.



	Yellow for flammable liquids
	Red for paints, inks, and other combustible liquids
	Blue for corrosives and hazardous liquids
	Green for pesticides and insecticides
	Silver or neutral colors for laboratory settings
	White, beige or gray for waste or outdoor lockers

#### Self-Close

This style self-indexes and self-latches to automatically shut doors upon release. Mechanism is concealed in the top wall, maximizing available shelf space. Fusible links hold doors open during use. In the event of a fire, fusible links will melt at 165°F (74°C) to automatically close doors.



Concealed mechanism



Fusible link

## How to maintain a cabinet

**Always store chemicals in closed containers.**

Clean up spills promptly. Be sure cabinet is level and located indoors in a well ventilated, low humidity environment. Never drill into a cabinet wall—this will negate the FM approval. Ensure cabinet doors are fully operational—that they properly close and engage the three-point latch.



for Flammables



Using multiple cabinets helps you organize and segregate dangerous liquids.

## Sure-Grip® EX Safety Cabinets for Flammables

**Safety cabinets offer safe, dependable flammable liquid storage and protection**

Protect workers, reduce fire risks, and improve productivity by storing flammable fuels and chemicals in code-compliant safety cabinets. Designed to meet OSHA and NFPA 30 standards, Sure-Grip® EX cabinets are constructed of sturdy 18-gauge (1-mm) thick double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space for fire resistance. High-performance, self-latching doors close easily and securely for maximum protection under fire conditions. Fail-safe closing mechanism ensures three-point stainless steel bullet latching system works every time.

For added security, U-Loc™ handle comes with a cylinder lock and key set or accepts an optional padlock.

Haz-Alert™ reflective warning labels are highly visible under fire conditions or during power outages when illuminated with a flashlight.

Patented SpillSlope® galvanized steel shelves direct spills to back and bottom of a leakproof sump. They adjust on 3-in (76-mm) centers for versatile storage. Cabinets also feature a leakproof 2-in (51-mm) bottom sump, dual vents with flame arresters, four adjustable self-leveling feet, grounding connector and trilingual warning label. Durable lead-free epoxy/polyester powder-coat finish provides excellent chemical resistance.

All cabinets are FM-approved and come with a ten-year warranty.

Self-closing models also meet NFPA 1 and the International Fire Code. They shut and latch automatically when a fusible link melts at 165°F (74°C) under fire conditions. Unique, concealed self-closing mechanism offers obstruction-free access to contents.



8945001



8945201



8930001



8960001



Capacity Gallons/Liters	Number of Doors and Style	Dimensions H x W x D		Adj Shelves	Sump Capacity Gallons/Liters	Approv/Lstg Regulation	Sure-Grip® Model No	Ship Wt lb/kg	Extra Shelf Model No
		Exterior	Interior						
30/114	2 door, manual	44 x 43 x 18 in	39.625 x 39.5 x 14.562 in	1	5.2/19.7	FM,N,O,A	8930001	231/105	29937
	2 door, self-close	1118 x 1092 x 457 mm	1006 x 1003 x 370 mm			FM,N,O,A,I	8930201	238/108	
45/170	2 door, manual	65 x 43 x 18 in	60.5 x 39.5 x 14.562 in	2	8.3/31.5	FM,N,O,A	8945001	311/141	29944
	2 door, self-close	1651 x 1092 x 457 mm	1537 x 1003 x 370 mm			FM,N,O,A,I	8945201	313/142	
60/227	2 door, manual	65 x 34 x 34 in	60.5 x 30.75 x 30.34 in			FM,N,O,A	8960001	388/176	
	2 door, self-close	1651 x 864 x 864 mm	1537 x 781 x 771 mm			FM,N,O,A,I	8960201	392/178	
90/341*	2 door, manual	65 x 43 x 34 in	60.5 x 39.5 x 30.34 in	2	10.7/40.6	FM,N,O,A	8990001	481/218	29945
	2 door, self-close	1651 x 1092 x 864 mm	1537 x 1003 x 771 mm			FM,N,O,A,I	8990201		

\*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454L) of Category 4 flammable liquids may be stored in a safety cabinet.