

SlimFit™ Gate EasyFit™ Gate EasyFit™ XL Gate

Self-Closing Gates

Meets OSHA Requirements

1910.29(b) and 1926.502(b)

OSHA compliant gates that protect workers from falls, or limit access to hazardous areas.

Features

Stop measuring and simplify installation logistics with the most versatile self-closing gates available.

- SlimFit: Fits openings between 14" and 30"
- EasyFit: Fits openings from 17" to 48"
- EasyFit XL: Fits openings from 17" to 60"
- Universal system mounts to 1- 2" round or square posts and can be wall mounted.
- Prevent access from hazards by adding a locking hasp

Color Options

EasyFit and EasyFit XL

- Available in yellow/galvanized or all galvanized.

SlimFit

- yellow/galvanized only.



Why Choose Garlock Safety Systems™?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- In-House Engineering
- Full Passive Fall Prevention Portfolio
- Custom Engineered Products Available

Features



Universal Clamp Mount



Slotted for Lock-out Clasp



SlimFit gate for narrow openings

Specifications

- Closing method: Spring Loaded
- SlimFit: Fits openings between 14" and 30"
- EasyFit: Fits openings from 17" to 48"
- EasyFit XL: Fits openings from 17" to 60"
- Mounts to 1-2" square or round posts and can be wall mounted
- Hinges feature vertical height adjustability for application versatility
- SlimFit requires tubes be cut for a perfect fit

Part Numbers

Part Number	Description
412-001-001	SlimFit gate for 14" to 30" openings, yellow plate and galvanized slide
301534	EasyFit gate for 17" to 48" openings, yellow plate and galvanized slide
301525	EasyFit gate for 17" to 48" openings, galvanized plate and galvanized slide
301555	EasyFit XL gate for 17" to 60" openings, yellow plate and galvanized slide
301556	EasyFit XL gate for 17" to 60" openings, galvanized plate and galvanized slide

GARLOCK
SAFETY SYSTEMS

P : 877.791.4446
E : safetyorders@garlockequip.com
GARLOCKSAFETY.COM

Address:
2601 Niagara Ln N.
Plymouth, MN 55447