



Micrometer Torque Wrench

- Calibrated and certified to +/-3% of torque reading clockwise.
- Calibrated and certified to +/-6% of torque reading counter clockwise.
- Audible click when desired torque is reached. Wrench automatically resets itself.
- Retains Calibration for 30,000 cycles.
- Certified models can be ordered calibrated and certified to +/-2% in either direction.
- Preset torque wrenches available upon request.

FIXED HEAD

Product		Drive		
ID No.	Torque Range	Size	Length	Box No.
J6061C	40-200 in/lbs	1/4"	12"	6006PBF
J6063C	40-200 in/lbs	3/8"	12"	6006PBF
J6065C	100-1000 in/lbs	3/8"	15-5/8"	6006PBF
J6005C	10-80 ft/lbs	3/8"	15-1/2"	6006PBF
J6015C	30-150 ft/lbs	1/2"	21-5/8"	6014PBF
J6013C	50-250 ft/lb	1/2"	27"	6014PBF
J6017AB	90-600 ft/lb	3/4"	41-1/2"	6007PBF
J6023	200-1000 ft/lbs	1"	69"	N/A
J6025	300-2000 ft/lbs	1"	107-1/2"	N/A

ANSI SPEC.: B107.14M

RATCHET HEAD

KAICHEI HI	AD			
Product			Drive	
ID No.	Torque Range	Size	Length	Box No.
J6006C	10-80 ft/lbs	3/8"	15-1/2"	6006PBF
J6006NMC	10-80 Nm	3/8"	15-1/2"	6006PBF
J6006MC*	10-80 Nm Only	3/8"	15-1/2"	6006PBF
J6012C	20-100 ft/lbs	3/8"	17-1/4"	6006PBF
J6008C	10-80 ft/lbs	1/2"	15-1/2"	6006PBF
J6016C	30-150 ft/lbs	1/2"	21-5/8"	6014PBF
J6016NMC	40-200 Nm	1/2"	21-5/8"	6014PBF
J6016MC*	40-200 Nm Only	1/2"	21-5/8"	6014PBF
J6014C	50-250 ft/lb	1/2"	27"	6014PBF
J6014NMC	70-350 Nm	1/2"	27"	6014PBF
J6014MC*	70-350 Nm Only	1/2"	27"	6014PBF
J6018AB	60-300 ft/lbs	3/4"	32-11/16"	6007PBF
J6020AB	90-600 ft/lbs	3/4"	41-1/2"	6007PBF
J6020NM	120-800 Nm	3/4"	41-1/2"	6007PBF
J6022B	140-700 ft/lbs	1"	48"	6007PBF
J6062C	40-200 in/lbs	1/4"	12"	6006PBF
J6064C	40-200 in/lbs	3/8"	12"	6006PBF
J6066C	100-1000 in/lbs	3/8"	15-5/8"	6006PBF
J6068C	300-1800 in/lbs	1/2"	20-7/8"	6014PBF
J6072C	600-3000 in/lbs	1/2"	27"	6014PBF

ANSI SPEC.: B107.14M