

# RESCUE HOOK & STATIC DISCHARGE STICK

**INSULATED RESCUE HOOK** - Salisbury's insulated rescue hook is an invaluable tool for any workplace. It is used to release a victim from contact. Confined spaces, in vaults, or just near electrical cabinets and switch gear are some of the places where this tool is a must. Insulated rescue hooks feature a foam-filled, fiberglass reinforced handle for superior electrical insulation and a coated, heat treated body hook with an 18" opening and are made in accordance with ASTM Standard F711. The stick is available in the standard lengths of 6 and 8 feet. Other lengths are available as a special order. Contact us with your requirements.

**STATIC DISCHARGE STICK** - The Static Discharge Stick is designed to safely remove the static charge after de-energizing. This tool is pre-assembled and includes a brass alloy "U" hook, closed cell foam-filled tubular fiberglass switch stick made in accordance with ASTM Standard F711. Static discharge sticks have 6 feet of copper grounding cable attached to a Salisbury 1814 flat jaw, grade 3, bronze serrated clamp with strain relief.

CAT. NO.	DESCRIPTION / ft. (m)	WEIGHT lbs. (kgs)
<b>INSULATED RESCUE HOOK</b>		
24400	Rescue Hook 3' (0.9 m) length	3.4 (1.5)
24401	Rescue Hook 6' (1.8 m) length	4.5 (2)
24403	Rescue Hook 8' (2.4 m) length	5.5 (2.5)

<b>STATIC DISCHARGE STICK</b>		
20817	Static Discharge Stick OAL 3'8" (1.08 m) length	8 (3.6)
22629	Static Discharge Stick w/ Universal Attachment 1' (0.3 m) length	.38 (0.17)



**WARNING: DISCHARGE STICKS ARE NOT GROUNDING TOOLS AS DESCRIBED BY OSHA 1910.269 AND CARRY NO FAULT DUTY RATING.**

