

Product Datasheet uvex 2 xenova 9558.1 - .3 S1 P SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

General features	<ul style="list-style-type: none">• Low weight and modern perforated S1 P safety shoe• Perforated microvelour• Suitable for people allergic to chrome as it's made from synthetic materials• All sole materials are free of silicones, plasticisers and other paint wetting impairment substances• BOA® Fit System for a fast, effortless, precision fit
Protection features	<ul style="list-style-type: none">• Meets ESD requirements: resistance to ground < 35 megaohm• 100% metal-free uvex xenova® toe cap. Compact design, anatomical shape, good lateral stability, no thermal conductivity properties• Metal-free, penetration-resistance insole in accordance with the latest standard, which does not impact shoe flexibility• Ergonomically designed outsole made from dual density polyurethane with excellent slip resistance
Comfort features	<ul style="list-style-type: none">• Light weight and optimised shock absorption• Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials• Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot• Soft padding on collar
Outsole	<ul style="list-style-type: none">• PUR outsole, non-marking

	<ul style="list-style-type: none"> • Ergonomically designed tread • Extremely flexible, excellent shock absorption • Unique PUR outsole system makes the shoe ultra-light • Two-layer system with abrasion-resistant and cut-resistant outsole • Excellent slip resistance • Self-cleaning tread • Resistant to oil and petrol • Resistant to temperatures for short periods up to ca. +120°C 																
Certificates	<ul style="list-style-type: none"> • Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions. 																
Areas of application	<ul style="list-style-type: none"> • Medium applications 																
Technical data	<table> <tr> <td>Art.-no.</td> <td>9558.1</td> <td>.2</td> <td>.3</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> </tr> <tr> <td>Standard</td> <td colspan="3">EN ISO 20345:2011 S1 P SRC</td> </tr> <tr> <td>Size</td> <td colspan="3">38 – 52</td> </tr> </table>	Art.-no.	9558.1	.2	.3	Width	10	11	12	Standard	EN ISO 20345:2011 S1 P SRC			Size	38 – 52		
Art.-no.	9558.1	.2	.3														
Width	10	11	12														
Standard	EN ISO 20345:2011 S1 P SRC																
Size	38 – 52																
Accessories	<p><i>comfortable climatic insole</i> (Article-no.: 9534.7-9)</p> <ul style="list-style-type: none"> • Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones • Ultra breathable and moisture-absorbing materials • Shock absorption zones that assist natural movement • Non-irritating, comfortable surface structure 																