

# 833 Switchboard Matting™ Class 1

Class 1 Insulation Matting



#### Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting 833 Switchboard Matting™ Class 1

Insulating matting prevents workers from being "grounded" and provides safety in case of electrical shock. The corrugated saw-tooth top surface increases traction and is easy to sweep clean.

- Each square inch of matting is tested in conformance with ANSI/ASTM D-178 specifications
- The corrugated saw-tooth top surface provides increased traction and is easy to sweep clean
- Must be replaced every 12 months for optimum safety
- Recommended maximum usage: 7,500 Volts

#### Recommended use

- Dry Areas
- Around electric sub-stations, transformers and switches, electrical panels, engine and generator
- Heavy duty

#### Colors:

Black

#### Sizes:

- 91cm x 150cm
- 91cm x linm
- 91cm x 22,8m

















# Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting $\mathsf{Switchboard}$ Matting $\mathsf{TM}$ Class 1

#### General

| Brand             | Notrax                                                                                                 |  |
|-------------------|--------------------------------------------------------------------------------------------------------|--|
| Category          | Switchboard Matting                                                                                    |  |
| Product Number    | 833                                                                                                    |  |
| Product Family    | Industrial & Commercial Matting                                                                        |  |
| Product Group     | Ergonomic, Anti-fatigue & Safety Matting                                                               |  |
| Product Name      | Switchboard Matting™ Class 1                                                                           |  |
| Recommended use   | Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms |  |
| Shipping Location | Barendrecht 2992SB, The Netherlands                                                                    |  |
| Туре              | Industrial Specialties - Electrical Protective Matting                                                 |  |
| Update trigger    | 20210310-1301                                                                                          |  |
| Usage Intensity   | Heavy duty                                                                                             |  |

## Sustainability

| Reach EU | Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals). |
|----------|-----------------------------------------------------------------------------------------|
|----------|-----------------------------------------------------------------------------------------|

### Tests

| Hardness             | 75 Shore A |
|----------------------|------------|
| Surface Flammability | Pass       |

## **Technical Specifications**

| Application         | Dry industrial environments |
|---------------------|-----------------------------|
| Edges               | No borders                  |
| Material            | PVC (DOP free)              |
| Material Group      | PVC                         |
| Process             | Calendering                 |
| Voltage Class       | 1                           |
| Voltage Maximum     | 10000                       |
| Voltage Recommended | 7500                        |

## Switchboard Matting™ Class 1 Black

| Art. nr.   | Dimension (cm) | Weight (kg) | Height (cm) |
|------------|----------------|-------------|-------------|
| 833C0036BL | 91cm x linm    | 7.6         | 0.47        |
| 833R0375BL | 91cm x 22,8m   | 160         | 0.47        |
| 833S0035BL | 91cm x 150cm   | 11.6        | 0.47        |