

B1610 - T-REX TOP/T-WALL TOP

Collection: Fortrex

Upper: Water-Resistant Nubuck

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Midsole: Polyurethane

Toecap: SlimCap

Sole: Rubber

Outer Carton: 5

Fortrex

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

Standards

EN ISO 20345:2022 S3S (HRO CI HI LG SC FO SR)



Features

- Men's Width 12
- Women's Width 10.5
- 200 joules resistant toe-cap
- Anti-static footwear
- Shock absorption in the heel region
- WPA
- Puncture Resistant 3mm
- Heat resistant 1 minute up to 300°C
- Hydrocarbons resistant
- Cold insulation up to -17°C
- Heat insulation up to 150°C

PORTWEST®



B1610 - T-REX TOP/T-WALL TOP

Commodity Code: 6403993300

Test House

CIMAC (Notified Body No.: 0465)
Via Aguzzafame 60/b
27029, ITALIE
Cert No: N° F-113-05710-22 Rev. 1

CIMAC (Notified Body No.: 0465)
Via Aguzzafame 60/b
27029, ITALIE
Cert No: N° F-113-05710-22 Rev. 1

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
B1610BKO36	Black/Orange	68.0	55.0	38.0	1.6720	0.1421	8052530122808	
B1610BKO37	Black/Orange	68.0	55.0	38.0	1.7290	0.1421	8052530122815	
B1610BKO38	Black/Orange	68.0	55.0	38.0	1.8080	0.1421	8052530122822	
B1610BKO39	Black/Orange	78.0	36.0	40.0	1.8320	0.1123	8052530122839	
B1610BKO40	Black/Orange	78.0	36.0	40.0	1.8930	0.1123	8052530122846	
B1610BKO41	Black/Orange	78.0	36.0	40.0	1.9290	0.1123	8052530122853	
B1610BKO42	Black/Orange	78.0	36.0	40.0	2.0470	0.1123	8052530122860	
B1610BKO43	Black/Orange	78.0	36.0	40.0	2.0460	0.1123	8052530122877	
B1610BKO44	Black/Orange	78.0	36.0	40.0	2.2060	0.1123	8052530122884	
B1610BKO45	Black/Orange	78.0	36.0	40.0	2.3820	0.1123	8052530122891	
B1610BKO46	Black/Orange	78.0	36.0	40.0	2.3600	0.1123	8052530122907	
B1610BKO47	Black/Orange	78.0	36.0	40.0	2.4860	0.1123	8052530122914	
B1610BKO48	Black/Orange	78.0	36.0	40.0	2.4800	0.1123	8052530122921	