




SOLUTION SELLING GUIDE

There's a Ladder Solution for Every Job.



Selecting the Right Ladder.

LADDER STYLES





SINGLE-SIDED **STEPLADDER**

- Industry standard stepladder has now been upgraded
- Includes LOCKTOP™ and EDGE360™





TWIN STEPLADDER

- Ideal for two-person jobs
- 300lbs capacity per side
- Includes LOCKTOP™ and EDGE360™





PODIUM & PLATFORM **LADDERS**

- Large platform for long standing comfort
- Includes EDGE360™





4) TRIPOD STEPLADDER

- Ideal for tight spaces
- Use between wall studs or hard to reach places
- Stable on uneven ground






EXTENSION LADDERS

- · Extends to varying lengths in one foot increments
- Access roof tops and higher elevations on construction sites
- Includes ALFLO® Rung Joints and SHU-LOK® features


LADDER HEIGHT

STEPLADDERS




Ladder Height	Maximum Reach
3'	7'
4'	8'
5'	9'
6'	10'
7'	11'
8'	12'
10'	14'
12'	16'

PODIUM & PLATFORM LADDERS



Platform Height	Maximum Reach
2'	8'
4'	10'
6'	12'
8'	14'
10'	16'

EXTENSION LADDERS




Ladder	Maximum
Height	Reach
16'	15'
20'	19'
24'	23'
28'	27'
32'	31'

Productivity, Durability & Quality



Maximize your productivity and increase your work space.







INTEGRATE Protects rail

INTEGRATED RAIL SHIELD

Protects rail during vehicle offloading and maneuvering on the jobsite



EDGE BRACING

Supports rail and step



OVER-SIZED FEET & FOOT PADS

Stability while you work



Available in 3', 4', 5', 6', 7', 8', 10' and 12' sizes

Load capacity combined weight of user and materials










Ideal ladder for multiple application needs




6200SERIES STEPLADDER

Model No.	Grainger No.	Size	Approx. Width	Approx. Spread	Approx. Shipping Wt. Lbs.
6203	41D245	3'	18-1/8"	23-1/8"	13.0
6204	3W421	4'	19-7/8"	29"	16.0
6205	3AZX1	5'	21-5/8"	35-1/8"	19.0
6206	3W141	6'	23-3/8"	41-1/4"	22.0
6207	3AZX2	7'	25-1/8"	47-1/2"	26.0
6208	3W142	8'	26-7/8"	53-5/8"	30.0
6210	3W183	10'	30-3/8"	65-7/8"	39.0
6212	3W422	12'	33-7/8"	78-1/4"	48.0











T6200SERIES TWIN STEPLADDER

Model No.	Grainger No.	Size	Approx. Width	Approx. Spread	Approx. Shipping Wt. Lbs.
T6203	41D246	3'	18-1/8"	29"	16.0
T6204	6YG79	4'	19-7/8"	36-1/8"	19.0
T6205	3AZX6	5'	21-5/8"	43-1/8"	23.0
T6206	6YG80	6'	23-3/8"	50-1/8"	27.0
T6208	6YG81	8'	26-7/8"	64-1/8"	37.0
T6210	3AZX7	10'	30-3/8"	78-1/8"	54.5
T6212	3AZX8	12'	33-7/8"	92-1/8"	68.5

PD7300SERIES PODIUM LADDER Type IAA, 375 lb. Duty Rating



The Podium Ladder is ideal for working at fixed heights, reaching all directions, and provides secure feel with wrap-around waist high guard rail.







PD6200SERIES PODIUM LADDER

Model No.	Grainger No.	Height (Size) to Platform	Rail Length	Approx. Width	Approx. Spread	Approx. Shipping Wt. Lbs.
PD6203	20KJ26	3'	6'	25.5"	36"	22.4
PD6204	20KJ27	4'	7'	27"	43"	27.7
PD6206	20KJ28	6'	9'	30.5"	55"	33.6
PD6208	20KJ29	8'	11	34"	67"	45.9
PD6210	20KJ30	10'	13'	37.5"	80"	57.0

PD7300SERIES PODIUM LADDER

Model No.	Grainger No.	Height (Size) to Platform	Rail Length	Approx. Width	Approx. Spread	Approx. Shipping Wt. Lbs.
PD7303	36FX50	3'	6'	26"	36"	23
PD7304	36FX51	4'	7'	27"	43"	28
PD7306	36FX52	6'	9'	31"	55"	34
PD7308	36FX53	8'	11	34"	67"	46

Available in 4', 6', 8', 10' and 12' sizes


Load capacity combined weight of user and materials



The Tripod Stepladder provides ease of access to your work environment, with back rail maneuverability to fit through studs, into tight areas, around corners and uneven surfaces







FTPSERIES TRIPOD STEPLADDER

Model No.	Grainger No.	Size	Approx. Width	Approx. Spread	Approx. Shipping Wt. Lbs.
FTP6204	4ZY19	4'	31"	30-1/2"	17.0
FTP6206	4EB99	6'	36"	43-3/4"	23.0
FTP6208	4ZY20	8'	40"	57"	31.0
FTP6210	41D249	10'	51"	71"	42.0
FTP6212	41D250	12'	54"	77-3/4"	51.0

Available in 4', 6', 8', 10' and 12' sizes

Load capacity combined weight of user and materials







- Customized HolsterTop[™] secures tools from falling
- Convenient conduit cutting system (not available on the 4 foot model)
- Built-In wire spool holders for both large and small spools
- Rugged professional grade bracing



OBELOOSERIES **ELECTRICIAN'S JOBSTATION**

Model No.	Grainger No.	Size	Approx. Width	Approx. Spread	Approx. Shipping Wt. Lbs.
OBEL04	1FCF1	4'	19-7⁄8"	29"	16.0
OBEL06	1FCF2	6'	23-3⁄8"	41-1/4"	24.0
OBEL08	1FCF3	8'	26-7/8"	53-5⁄8"	32.0
OBEL10	1FCF4	10'	30-3⁄8"	65-7/8"	41.0
OBEL12	1FCF5	12'	33-7/8"	78-1/4"	51.5

MTSERIES TELESCOPING MULTILADDER

Available in 3'-5', 4'-7', 5'-9' and 6'-11' stepladder sizes

Type IA, 300 lb. Duty Rating per side

Load capacity per side combined weight of user and materials





POSITION #1Twin Stepladder



POSITION #2
Stairway Stepladder



POSITION #3 Extension Ladder



POSITION #4
Self-Supporting
2-Scaffold


MTSERIES TELESCOPING MULTILADDER

Model No.	Grainger No.	Stepladder Height	Extension Height	Stair Height	Scaffold Length	Approx. Shipping Wt. Lbs.
MT-13	2NKW6	3' to 5'	7' to 11'	3' to 5'	1' to 2'	31.5
MT-17	2NKW7	4' to 7'	9' to 15'	4' to 7'	1' to 3'	39.5
MT-22	2NKW8	5' to 9'	11' to 19'	5' to 9'	1' to 4'	47.0
MT-26	2NKW9	6' to 11'	13' to 23'	6' to 11'	1' to 5'	62.6

Available in 16', 20', 24', 28, 32' and 40' sizes

Load capacity combined weight of user and materials





Smooth operating 1-5/8" Slippulley with polypropylene resistant rope TRACTION-TRED® D-rungs Seven layer fiberglass **Heavy Duty** construction extruded rung locks are spring loaded to operate smoothly

D6200-2SERIES EXTENSION LADDER

Model No.	Grainger No.	Total Length of Sections	Max. Working Length	Approx. Shipping Wt. Lbs.
D6216-2	3W620	16'	13'	36.5
D6220-2	3W184	20'	17'	44.5
D6224-2	3W139	24'	21'	52.0
D6228-2	3W140	28'	25'	59.5
D6232-2	3W185	32'	29'	71.5
D6240-2	4XP10	40'	35'	88.5

D6200-3SERIES **COMPACT EXTENSION LADDER**

Type IA, 300 lb. Duty Rating

Available in 16', 20', 24', 28, and 32' sizes

Load capacity combined weight of user and materials



Innovative 3-section design allows for:


- Storing convenience and maneuverability
- Ease of transport on compact vehicles
- · Versatility use indoors or outdoors





D6200-3SERIES EXTENSION LADDER

Model No.	Grainger No.	Total Length of Sections	Max. Working Length	Approx. Shipping Wt. Lbs.
D6216-3	22E977	18'	13'	40.5
D6220-3	22E978	23'	17'	54.0
D6224-3	22E979	27'	21'	61.0
D6228-3	22E980	31'	25'	74.5
D6232-3	22E981	35'	29'	81.0



D7200-2SERIES LIGHTWEIGHT EXTENSION LADDER Type IAA, 375 lb. Duty Rating

Load capacity combined weight of user and materials



D6400-2SERIES LIGHTWEIGHT EXTENSION LADDER

	Model No.	Grainger No.	Total Length of Sections	Max. Working Length	Approx. Shipping Wt. Lbs.
	D6416-2	36FX54	16'	13'	32
ſ	D6420-2	36FX55	20'	17'	40
	D6424-2	36FX56	24'	21'	46
	D6428-2	36FX57	28'	25'	53

D7200-2SERIES LIGHTWEIGHT EXTENSION LADDER

Model No.	Grainger No.	Total Length of Sections	Max. Working Length	Approx. Shipping Wt. Lbs.
D7216-2	36FX58	16'	13'	36
D7220-2	36FX59	20'	17'	44
D7224-2	36FX60	24'	21'	51
D7228-2	36FX61	28'	25'	58



LADDER SAFETY AND INSPECTION GUIDE



- Safety training manual
- Safety training DVD
- Ladder Safety Tips Brochures

LADDER SAFETY TRAINING KIT TRAINING MATERIALS

- Written guiz
- Downloadable literature CD
- Downloadable Ladder Inspection Form
- 8S1241



Stepladder	Size ft.	Van Na	Extension Ladder Sizeft	
Circle Areas of Damage	Aluminum Wood Loose, Cracked, B Rails: Cracked, Bent, Sp Rail Shields Labels: Missing or Not Rei Loose, Bent, Missing or Not Rei Loose, Bent, Cracked, Loose or Spreader: Loose, Bent or Brogeneral: Rust, Corrosion or Other: Bracing, Shoes, Rader is in good conditions.	lit or Frayed adable	Rungs: Loose, Cracked, Bent or Missing Rails: Cracked, Bent, Split or Frayed Labels: Missing or Not Readable Rung Locks: Loose, Bent, Missing or Broken Hardware: Missing, Loose or Broken Shoes: Worn, Broken or Missing Rope/Pulley: Loose, Bent or Broken Other: Bracing Rivets General: Rust, Corrosion or Loose Actions: Ladder tagged as damaged & removed Ladder is in good condition	Yes No



www.wernerco.com

For more information contact your Grainger Representative or visit Grainger.com®

