

## **Breathing Protection**

TD-09420-02

Product data sheet cup shape mask FFP2 NR D with Carbon, EN 149:2001 – uvex silv-Air 2220



## UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product features	<ul> <li>Particle-filtering cup shape mask with exhalation valve</li> <li>Protection level FFP2</li> <li>Soft material edges for high wearing comfort</li> <li>Continuous head band for a comfortable and secure fit</li> <li>Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li> <li>Flexible and adjustable nose clip</li> <li>Compatible with uvex safety eyewear</li> <li>Soft sealing lip guarantees a secure, comfortable sealed position of the mask</li> <li>Activated carbon filter for odors, gases and vapors below limit value</li> <li>Mask fulfils the requirements of the dolomite dust test (D)</li> </ul>	
Materials	Headband: textile Nose clip: aluminum Filter / mask: Melt Blown PP, Polyester Sealing lip: PVC foam Valve: ABS	

Date: 14.09.2016 Page 1 of 2

Areas of use	Mining, chemical industry, shipyards,	
The respiratory protection mask can be	iron and steel industry, woodworking,	
used against solid, aqueous and non-	dust and fumes of substances such as	
volatile liquid aerosols up to <b>10 times</b>	asbestos, quartz, aluminum, copper,	
the respective limit values.	barium, titanium, vanadium, chrome,	
	manganese and coal dust with more	
	than 10% free silicon dioxide.	
Weight	20 g	
Standard	EN 149:2001 + A1:2009	

## Versions

Article number	Colour/Version	Retail unit
8732.220	cup shape mask FFP2, white with valve	15 pieces per box
	and carbon	

Date: 14.09.2016 Page 2 of 2