

# TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION



## F600 SERIES

### F621 - FFP2 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK

Product Code: BGV120-000-Q00 / BGV120-000-T00



#### Description

Vertical fold flat respirator with foam padded adjustable nose clip

#### Options

Box of 40 code: BGV120-000-Q00

Box of 15 x2 pack masks retail code: BGV120-000-T00



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.  
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)  
Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com).  
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.  
Page 1 of 3 / Issued 25 Jan 2021 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



[www.jspsafety.com](http://www.jspsafety.com)

[sales@jspsafety.com](mailto:sales@jspsafety.com)


UK tel: +44 (0)1993 826050

## FEATURES



### FOLDS FLAT

Fold flat design is compact and easy to carry in a pocket



### FOAM PADDED NOSE BRIDGE,

A mouldable nose bridge and foam pad on the inside for comfort and a firmer fit



### TOGGLE STRAPS,

Metal free, toggle adjustable straps create a firm and adaptable fit

## COMPATIBLE PRODUCTS

EVO® Gas Goggle  
EVO® Goggle Double Lens  
EVO® Goggle Single Lens  
Sonis® Compact Ear Defenders  
Sonis®1 Ear Defenders  
Sonis®2 Ear Defenders  
Sonis®3 Ear Defenders  
Stealth™ 16G  
Stealth™ 7000  
Stealth™ 8000  
Stealth™ 9000  
Stealth™ Coverlite™ Overspec  
Thermex™ Double Lens Goggle

## SAFETY STANDARDS

EN 149:2001 + A1:2009

## CERTIFICATION

CE 0370-4691-PPE/B issued by APPLUS

## SPECIFICATIONS

Classification

FFP2 (Filtering Facepiece Particulate)

Filter Type

P (Protects Against Solid and Liquid Aerosols)

Usage

NR (Non-Reusable)

Activated Carbon Layer

No

Minimum Filtration Efficiency

94% For FFP2 Rated

Maximum Total Inward Leakage (TIL)

8%

Nominal Protection Factor (NPF)

12

UK Assigned Protection Factor (APF)

10

Mask Design

Vertical Fold Flat

Exhalation Valve

No

Toggle Adjustment Straps

Yes

Nose Bridge

Moulded in mask

Mask Material

Polypropylene

Filter Shelf Life

5 Years

Product Weight

16g (Approx)



## ACCESSORIES

Portacount/AccuFIT Quantitative/Qualitative Face Fit Testing Kit & Spares

## APPLICATIONS

- Mining, Aggregates and Quarrying
- Agriculture
- Forestry & Landscaping
- Manufacturing
- Construction & Infrastructure
- Scaffolding & Roofing
- Welding (mild)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com.

Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 25 Jan 2021 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



## INSTRUCTIONS FOR USE

- Mask must be fitted in accordance with the instructions supplied
- Care must be taken to ensure that the correct mask type is selected for the work to be carried out
- If in doubt as to the type of mask required, seek professional guidance

## CLEANING & MAINTENANCE

- Not Applicable - Disposable Product
- Store the masks out of sunlight away from chemicals in a dry atmosphere

## DIMENSIONS OF MASK

- Depth: 12.5cm / Width: 15cm

## DIMENSIONS OF BOX

- Depth: 13cm / Width: 13cm / Height: 21cm

## DIMENSIONS OF OUTER PACKAGING

- Quantity: 1,200 (30 inner packs of 40 masks)
- Quantity: 450 (30 inner packs of 15 x 2 masks, retail packs)
- Depth: 670mm / Width: 410mm / Height: 440mm

## LIMITATIONS OF USE

- Protection will only be offered if the mask is fitted correctly
- The mask, when in contact with the skin may cause allergic
- Do not use where exposure to chemical gases may be experienced
- Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres
- Ensure good seal around the face is created before entering the hazard area
- The working life of the mask is nominally one day (this is based on a working day shift of 8 hours), however it may be affected by many factors, including work rate, airflow and concentration of any contaminant in the atmosphere. The mask should be changed immediately if,
  - a.) Breathing difficulties due to clogging are experienced,
  - b.) Breakthrough of a contaminant is detected by smell, taste or any other means, or
  - c.) The mask becomes damaged

