

## MAILLON RAPIDE QUICK LINKS



Quick Links, or also commonly known as screw links, are gaining popularity for use in situations for which carabiners are not recommended, such as when tri-axial loading cannot be avoided. The Delta shape can be used to rig anchors. The Delta can be used as a chest harness connector. While slower to open and close than a carabiner, they can be more secure when tightened down — and they cost less.

### Working-At-Height / Industrial Rope Access / Technical Rope Rescue

Working at height requires reliable, quality equipment. The Maillon Rapide Quick Links can be used with confidence in work-at-height maneuvers for industrial rope access or technical rope rescue when used in accordance with the regulatory safety standards they fall under. Always use life safety equipment and gear according to the regulatory safety standards for which it is classified and/or certified.

Option	Delta, 6 mm
Item	205002
PRODUCT WEIGHT	1.4 OZ (40 G)
BAR DIAMETER	6 MM
INSIDE LENGTH	1-3/4 IN (44 MM)

MATERIAL	STAINLESS STEEL
WORKING LOAD	4.4 KN (992 LBF)
BREAKING LOAD	22 KN (4950 LBF)
Option	Delta, 10 mm
Item	382101
PRODUCT WEIGHT	5.3 OZ (150 G)
BAR DIAMETER	10 MM
INSIDE LENGTH	2-5/8 IN (67 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	8.8 KN (1,984 LBF)
BREAKING LOAD	44.1 KN (9,920 LBF)
Option	Delta, 12 mm
Item	382121
PRODUCT WEIGHT	9.1 OZ (258 G)
BAR DIAMETER	12 MM
INSIDE LENGTH	3-3/16 IN (81 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	10.8 KN (2,425 LBF)
BREAKING LOAD	53.9 KN (12,125 LBF)
Option	Oval, 5 mm
Item	383051
PRODUCT WEIGHT	1.3 OZ (37 G)
BAR DIAMETER	5 MM
INSIDE LENGTH	1-9/16 IN (40 MM)
MATERIAL	STAINLESS STEEL
WORKING LOAD	4.4 KN (992 LBF)
BREAKING LOAD	22.1 KN (4960 LBF)
Option	Oval, 7 mm
Item	383071
PRODUCT WEIGHT	1.8 OZ (51 G)
BAR DIAMETER	7 MM

<b>INSIDE LENGTH</b>	2-1/16 IN (52 MM)
<b>MATERIAL</b>	GALVANIZED STEEL
<b>WORKING LOAD</b>	5.4 KN (1,213 LBF)
<b>BREAKING LOAD</b>	27 KN (6,065 LBF)
<hr/>	
<b>Option</b>	Oval, 12 mm
<b>Item</b>	383121
<b>PRODUCT WEIGHT</b>	8.2 OZ (233 G)
<b>BAR DIAMETER</b>	12 MM
<b>INSIDE LENGTH</b>	3-3/16 IN (81 MM)
<b>MATERIAL</b>	GALVANIZED STEEL
<b>WORKING LOAD</b>	14.7 KN (3,307 LBF)
<b>BREAKING LOAD</b>	73.6 KN (16,535 LBF)
<hr/>	
<b>Option</b>	Long Oval, 10 mm
<b>Item</b>	384101
<b>PRODUCT WEIGHT</b>	5.6 OZ (159 G)
<b>BAR DIAMETER</b>	10 MM
<b>INSIDE LENGTH</b>	3-3/8 IN (86 MM)
<b>MATERIAL</b>	GALVANIZED STEEL
<b>WORKING LOAD</b>	9.8 KN (2,205 LBF)
<b>BREAKING LOAD</b>	49 KN (11,025 LBF)
<hr/>	
<div> 1-800-235-5741 info@cmcpro.com cmcpro.com </div>	